




WERNER FISCHER AG
STAHLROHRE



Rundrohre

diverse Legierungen

geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301	1.4307	1.4404	1.4404
mm	mm	kg/m	ungegl.	geglüht	ungegl.	geglüht
6.0	1.0	0.12	x	x	x	x
8.0	1.0	0.17	x	x	x	x
8.0	1.5	0.24	x			
10.0	1.0	0.22	x	x	x	x
10.0	1.5	0.31	x	x		x
12.0	1.0	0.27	x	x	x	x
12.0	1.5	0.39	x	x	x	x
12.0	2.0	0.49	x			
13.0	1.0	0.30	x			
13.0	1.5	0.43	x			
13.5	1.6	0.47	x	x	x	x
13.5	2.3	0.63			x	x
14.0	1.0	0.32	x	x	x	x
14.0	1.5	0.46	x		x	
14.0	2.0	0.59	x			x
15.0	1.0	0.35	x	x	x	x
15.0	1.5	0.50	x	x	x	x
15.0	2.0	0.64	x			
16.0	1.0	0.37	x	x	x	x
16.0	1.5	0.54	x	x		x
16.0	2.0	0.69	x	x		
17.0	1.0	0.39	x	x	x	x
17.2	1.0	0.40	x			
17.2	1.5	0.58	x			
17.2	1.6	0.62	x	x	x	x
17.2	2.3	0.84	x	x	x	x
17.2	2.5	0.91	x			
18.0	1.0	0.42	x	x	x	x
18.0	1.5	0.61	x	x	x	x
18.0	2.0	0.79	x			
20.0	1.0	0.47	x	x		x
20.0	1.5	0.68	x	x	x	x
20.0	2.0	0.89	x	x	x	x
21.3	1.5	0.73	x			
21.3	1.6	0.78	x	x	x	x
21.3	2.0	0.95	x	x	x	x



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301	1.4307	1.4404	1.4404
mm	mm	kg/m	ungegl.	geglüht	ungegl.	geglüht
21.3	2.5	1.16	x			
21.3	2.6	1.20	x	x	x	x
22.0	1.0	0.52	x	x		x
22.0	1.2	0.62	x	x	x	x
22.0	1.5	0.76	x	x	x	x
22.0	2.0	0.99	x	x		
23.0	1.5	0.79	x	x	x	x
24.0	1.5	0.83	x			
25.0	1.0	0.59	x			
25.0	1.5	0.87	x	x	x	x
25.0	2.0	1.13	x	x	x	x
26.9	1.5	0.94	x			
26.9	1.6	1.00	x	x	x	x
26.9	2.0	1.23	x	x	x	x
26.9	2.5	1.50	x			
26.9	2.6	1.56	x	x	x	x
28.0	1.2	0.79	x	x	x	x
28.0	1.5	0.98	x	x		x
28.0	2.0	1.28	x	x		x
30.0	1.5	1.05	x	x	x	x
30.0	2.0	1.38	x	x	x	x
30.0	3.0	2.00	x			
32.0	1.5	1.13	x			
32.0	2.0	1.48	x	x	x	x
33.7	1.5	1.19	x			
33.7	1.6	1.27	x	x		x
33.7	2.0	1.56	x	x	x	x
33.7	2.5	1.92	x			
33.7	2.6	1.99	x	x	x	x
33.7	3.0	2.27	x			
33.7	3.2	2.41	x	x	x	x
35.0	1.5	1.24	x	x	x	x
35.0	2.0	1.63	x	x	x	x
35.0	2.5	2.00		x		
38.0	1.5	1.35	x	x	x	x
38.0	2.0	1.77	x	x		x



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301	1.4307	1.4404	1.4404
mm	mm	kg/m	ungegl.	geglüht	ungegl.	geglüht
38.0	2.6	2.27		x		
40.0	1.0	0.96	x		x	
40.0	1.5	1.42	x	x		
40.0	2.0	1.87	x	x	x	x
40.0	2.5	2.31	x			
40.0	3.0	2.74	x	x		
42.4	1.6	1.61	x	x		
42.4	2.0	1.99	x	x	x	x
42.4	2.5	2.46	x			
42.4	2.6	2.55	x	x	x	x
42.4	3.0	2.91	x			
42.4	3.2	3.09	x	x		x
43.0	1.5	1.53	x	x		
44.5	2.0	2.10	x	x	x	x
45.0	2.0	2.12	x			
48.3	1.5	1.73	x			
48.3	1.6	1.84			x	
48.3	2.0	2.28	x	x	x	x
48.3	2.6	2.93	x	x	x	x
48.3	3.0	3.35	x			
48.3	3.2	3.56	x	x	x	x
48.3	4.0	4.37	x			
50.0	1.5	1.79	x	x		
50.0	2.0	2.37	x	x		x
50.0	3.0	3.48	x			
51.0	1.5	1.83			x	
52.0	2.0	2.46	x	x	x	
53.0	1.5	1.90	x	x		x
54.0	2.0	2.56	x	x	x	x
60.3	1.5	2.17	x			
60.3	1.6	2.32	x			x
60.3	2.0	2.87	x	x	x	x
60.3	2.5	3.56	x			
60.3	2.6	3.70	x	x	x	x



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301	1.4307	1.4404	1.4404
mm	mm	kg/m	ungegl.	geglüht	ungegl.	geglüht
60.3	3.0	4.24	x			
60.3	3.2	4.50		x		x
60.3	3.6	5.03	x	x	x	x
63.5	2.0	3.03	x	x	x	x
69.0	2.0	3.30				x
70.0	2.0	3.35	x	x	x	x
70.0	2.9	4.80	x	x		x
76.1	2.0	3.65	x	x	x	x
76.1	2.3	4.18	x	x		x
76.1	2.5	4.54	x			
76.1	2.6	4.71	x	x	x	x
76.1	2.9	5.23			x	x
76.1	3.0	5.41	x			
76.1	3.2	5.75				x
76.1	3.6	6.43	x	x	x	
80.0	1.5	2.90	x			
80.0	2.0	3.85	x			
80.0	4.0	7.49	x			
84.0	2.0	4.04	x	x	x	x
88.9	2.0	4.28	x	x	x	x
88.9	2.3	4.91	x	x		x
88.9	2.5	5.32	x			
88.9	2.6	5.53	x	x	x	x
88.9	3.0	6.35	x			
88.9	3.05	6.45		x		
88.9	4.0	8.37	x	x		
88.9	4.05	8.47		x	x	
101.6	2.0	4.91	x			
101.6	3.0	7.29	x			
101.6	3.6	8.70	x			
103.0	1.5	3.75	x			
104.0	2.0	5.03	x	x	x	x



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen




geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m

Aussendurchmesser	Wandstärke	Gewicht	1.4301	1.4307	1.4404	1.4404
mm	mm	kg/m	ungegl.	geglüht	ungegl.	geglüht
108.0	2.0	5.23	x			
108.0	3.0	7.76	x			
108.0	4.0	10.25			x	
114.3	2.0	5.54	x	x	x	
114.3	2.5	6.89	x			
114.3	2.6	7.16	x	x	x	x
114.3	3.0	8.23	x			
114.3	3.2	8.76	x		x	
114.3	3.6	9.82	x		x	
114.3	4.0	10.88	x			
129.0	2.0	6.26	x		x	
131.0	3.0	9.47	x			
139.7	2.0	6.79	x		x	
139.7	2.6	8.79	x		x	
139.7	3.0	10.11	x		x	
139.7	3.2	10.77	x		x	
139.7	4.0	13.98	x			
154.0	2.0	7.49	x		x	
156.0	3.0	11.31	x		x	
168.3	2.0	8.20	x		x	
168.3	2.6	10.62	x		x	
168.3	3.0	12.22	x		x	
168.3	3.2	13.02	x		x	
168.3	5.0	20.13	x			
204.0	2.0	9.96	x		x	
206.0	3.0	15.01	x		x	
219.1	2.0	10.70	x		x	
219.1	2.6	13.88	x		x	
219.1	2.9	15.45	x		x	
219.1	3.0	15.98	x		x	
219.1	3.2	17.03	x		x	
254.0	2.0	12.42	x		x	
256.0	3.0	18.71	x		x	

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301	1.4307	1.4404	1.4404
mm	mm	kg/m	ungegl.	geglüht	ungegl.	geglüht
273.0	2.0	13.36	x		x	
273.0	2.6	17.33	x			
273.0	3.0	19.97	x		x	
273.0	4.0	26.52	x			
304.0	2.0	14.89	x		x	
306.0	3.0	22.41	x		x	
323.9	3.0	23.73	x		x	
355.0	2.5	21.72			x	
356.0	3.0	26.10	x		x	
406.0	3.0	29.80	x		x	
456.0	3.0	33.50	x			
506.0	3.0	37.20	x		x	



WERNER FISCHER AG
STAHLROHRE


Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301 / 1.4307	1.4404
mm	mm	kg/m		
4.00	1.00	0.07	x	
5.00	1.00	0.10	x	
6.00	1.00	0.12	x	x
6.00	1.50	0.17	x	x
6.00	2.00	0.20	x	
8.00	1.00	0.17	x	x
8.00	1.50	0.24	x	x
8.00	2.00	0.30	x	
9.00	1.00	0.20	x	
10.00	1.00	0.22	x	x
10.00	1.50	0.31	x	x
10.00	2.00	0.39	x	x
10.00	2.50	0.46	x	
10.20	1.60	0.34		x
10.20	2.00	0.40	x	x
12.00	1.00	0.27	x	x
12.00	1.50	0.39	x	x
12.00	2.00	0.49	x	x
13.00	1.50	0.43	x	
13.00	2.50	0.65	x	
13.50	1.60	0.47	x	x
13.50	2.30	0.63	x	x
14.00	1.00	0.32	x	x
14.00	1.50	0.46	x	
14.00	2.00	0.59	x	x
14.00	2.50	0.71	x	
14.00	3.00	0.81	x	
15.00	1.00	0.35	x	x
15.00	1.50	0.50	x	x
15.00	2.00	0.64	x	
16.00	1.00	0.37	x	
16.00	1.50	0.54	x	x
16.00	2.00	0.69	x	x
16.00	3.00	0.96	x	
16.00	4.00	1.18	x	



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301 / 1.4307	1.4404
mm	mm	kg/m		
17.00	1.00	0.39	x	
17.00	3.00	1.04	x	
17.20	1.60	0.62	x	x
17.20	2.00	0.75	x	
17.20	2.30	0.84	x	x
18.00	1.00	0.42	x	
18.00	1.50	0.61	x	x
18.00	2.00	0.79	x	
20.00	1.00	0.47	x	
20.00	1.50	0.68	x	x
20.00	2.00	0.89	x	x
20.00	2.50	1.08	x	x
20.00	3.00	1.26	x	
20.00	4.00	1.58	x	x
20.00	5.00	1.85	x	
21.30	1.60	0.78	x	x
21.30	2.00	0.95	x	x
21.30	2.60	1.20	x	x
21.34	3.73	1.62	x	
22.00	1.00	0.52	x	
22.00	1.50	0.76	x	x
22.00	2.00	0.99	x	
22.00	3.00	1.40	x	
22.00	4.00	1.77	x	
23.00	1.50	0.79	x	x
24.00	2.00	1.08	x	x
24.00	4.00	1.97	x	
25.00	1.00	0.59	x	
25.00	1.50	0.87	x	x
25.00	2.00	1.13	x	x
25.00	2.50	1.39	x	x
25.00	3.00	1.63	x	
25.00	4.00	2.07	x	
25.00	5.00	2.46	x	



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301 / 1.4307	1.4404
mm	mm	kg/m		
26.67	3.91	2.19	x	x
26.90	1.60	1.00	x	x
26.90	2.00	1.23		x
26.90	2.60	1.56	x	x
28.00	1.50	0.98	x	x
28.00	2.00	1.28	x	x
28.00	2.50	1.57	x	
28.00	5.00	2.83	x	
30.00	1.00	0.71	x	
30.00	1.50	1.05	x	
30.00	2.00	1.38	x	x
30.00	2.60	1.76	x	x
30.00	3.00	2.00	x	
30.00	5.00	3.08	x	
32.00	1.50	1.13	x	
32.00	2.00	1.48	x	x
32.00	2.50	1.82	x	
32.00	3.00	2.14	x	
32.00	4.00	2.76	x	
33.00	1.50	1.16	x	
33.00	4.00	2.86	x	
33.70	1.60	1.27	x	
33.70	2.00	1.56	x	x
33.70	2.60	1.99	x	x
33.70	3.20	2.41	x	x
34.00	2.00	1.58	x	
35.00	1.50	1.24	x	
35.00	2.00	1.63	x	x
35.00	2.50	2.00	x	
35.00	4.00	3.06	x	
36.00	2.00	1.68	x	
38.00	1.50	1.35	x	
38.00	2.00	1.77	x	x
38.00	2.50	2.19	x	
38.00	2.60	2.27	x	x



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301 / 1.4307	1.4404
mm	mm	kg/m		
38.00	3.00	2.59	x	
38.00	5.00	4.07	x	
40.00	1.00	0.96	x	
40.00	1.50	1.42	x	
40.00	2.00	1.87	x	x
40.00	2.50	2.31	x	
40.00	3.00	2.74	x	
40.00	5.00	4.31	x	x
42.16	3.56	3.39	x	x
42.40	2.00	1.99	x	x
42.40	2.60	2.55	x	x
42.40	3.20	3.09	x	x
43.00	1.50	1.53	x	
44.50	2.00	2.10	x	
44.50	2.60	2.69	x	x
44.50	2.90	2.97		x
45.00	1.50	1.61	x	
45.00	1.60	1.71	x	
48.26	5.08	5.41	x	
48.30	2.00	2.28	x	x
48.30	2.60	2.93	x	x
48.30	3.20	3.56	x	x
50.00	1.50	1.79	x	
50.00	2.00	2.37	x	x
50.00	2.50	2.93	x	
50.00	3.00	3.48	x	
50.00	5.00	5.55	x	x
51.00	2.60	3.10	x	
52.00	2.00	2.46	x	
54.00	2.00	2.56	x	x
55.00	2.50	3.24	x	
55.00	5.00	6.16	x	x
57.00	2.00	2.71	x	
57.00	2.90	3.87	x	x
57.00	6.50	8.09	x	



WERNER FISCHER AG
STAHLROHRE

Rundrohre

diverse Legierungen




geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m

Aussendurchmesser	Wandstärke	Gewicht	1.4301 / 1.4307	1.4404
mm	mm	kg/m		
60.00	5.00	6.78	x	
60.30	2.00	2.87	x	x
60.30	2.60	3.70	x	x
60.30	2.90	4.10		x
60.30	3.20	4.50	x	
60.30	3.60	5.03	x	x
63.50	2.60	3.90	x	x
64.00	2.00	3.06	x	
65.00	2.50	3.85	x	
70.00	2.00	3.35	x	
70.00	2.90	4.80	x	x
70.00	4.00	6.51	x	
70.00	4.50	7.27		x
75.00	2.50	4.47	x	
76.10	2.00	3.65	x	
76.10	2.60	4.71	x	x
76.10	2.90	5.23	x	x
76.10	3.60	6.43	x	x
80.00	2.00	3.85	x	
80.00	2.50	4.78	x	
80.00	4.00	7.49	x	
80.00	5.00	9.24	x	
85.00	2.50	5.08	x	
88.90	2.60	5.53	x	x
88.90	3.05	6.45	x	
88.90	3.20	6.76		x
88.90	3.60	7.57	x	
88.90	4.05	8.47	x	x
101.60	4.05	9.74	x	
101.60	5.74	13.56	x	
108.00	3.00	7.76	x	
108.00	4.00	10.25	x	x
108.00	6.30	15.79	x	
114.30	2.60	7.16	x	
114.30	3.05	8.36	x	

Rundrohre

diverse Legierungen



geschweisst, gebeizt, nach EN 10088 / 10217-7/ISO 1127, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht	1.4301 / 1.4307	1.4307
mm	mm	kg/m		
114.30	4.50	12.18	x	x
114.30	6.02	16.07	x	
114.30	8.56	22.31	x	
133.00	4.00	12.72		x
139.70	4.00	13.38	x	
141.30	6.55	21.76	x	
141.30	9.53	30.95	x	



WERNER FISCHER AG
STAHLROHRE

Vierkantrohre

diverse Legierungen



geschweisst, ungeglüht, metallblank, nach EN 10088, Stangenlänge ca. 6 m


Abmessung	Wandstärke	Gewicht	1.4301	1.4301	1.4404	1.4404
mm	mm	kg/m	blank	geschliffen	blank	geschliffen
10 x 10	1.0	0.28	x	x		
15 x 15	1.0	0.44	x			
15 x 15	1.5	0.64	x	x	x	
16 x 16	1.5	0.68	x	x		
20 x 20	1.0	0.60	x			
20 x 20	1.2	0.71	x			
20 x 20	1.5	0.87	x	x		
20 x 20	2.0	1.13	x	x	x	
22 x 22	1.5	1.00		x		
22 x 22	2.0	1.33		x		
25 x 25	1.2	0.90	x	x		
25 x 25	1.5	1.11	x	x	x	x
25 x 25	2.0	1.44	x	x	x	x
25 x 25	2.5	1.77	x			
25 x 25	3.0	2.07	x			
30 x 30	1.2	1.09	x	x		
30 x 30	1.5	1.34	x	x	x	x
30 x 30	2.0	1.76	x	x	x	x
30 x 30	2.5	2.16	x	x		
30 x 30	3.0	2.54	x	x	x	
35 x 35	1.0	1.07		x		
35 x 35	1.2	1.27	x	x		
35 x 35	1.5	1.58	x	x	x	
35 x 35	2.0	2.07	x	x	x	x
35 x 35	2.5	2.55	x			
35 x 35	3.0	3.01	x			
40 x 40	1.5	1.81	x	x		
40 x 40	2.0	2.39	x	x	x	x
40 x 40	2.5	2.94	x			
40 x 40	3.0	3.49	x	x	x	
40 x 40	4.0	4.52	x		x	
45 x 45	1.5	2.05		x		
45 x 45	2.0	2.70	x	x		
45 x 45	3.0	3.96	x			
50 x 50	1.5	2.28	x	x		
50 x 50	2.0	3.01	x	x	x	x
50 x 50	2.5	3.73	x			
50 x 50	3.0	4.43	x	x	x	



WERNER FISCHER AG
STAHLROHRE

Vierkantrohre

diverse Legierungen



geschweisst, ungeglüht, metallblank, nach EN 10088, Stangenlänge ca. 6 m

Abmessung	Wandstärke	Gewicht	1.4301	1.4301	1.4404	1.4404
mm	mm	kg/m	blank	geschliffen	blank	geschliffen
50 x 50	4.0	5.78	x	x	x	
50 x 50	5.0	7.07	x			
60 x 60	2.0	3.64	x	x	x	
60 x 60	2.5	4.51	x			
60 x 60	3.0	5.37	x	x	x	
60 x 60	4.0	7.03	x	x	x	
60 x 60	5.0	8.64	x			
70 x 70	3.0	6.31	x			
70 x 70	4.0	8.29	x			
70 x 70	5.0	10.21	x			
80 x 80	2.0	4.90	x	x	x	
80 x 80	2.5	6.08	x			
80 x 80	3.0	7.25	x	x	x	
80 x 80	4.0	9.55	x	x	x	
80 x 80	5.0	11.78	x		x	
80 x 80	6.0	13.94	x			
100 x 100	2.0	6.15	x	x		
100 x 100	2.5	7.65				
100 x 100	3.0	9.14	x	x	x	
100 x 100	4.0	12.06	x		x	
100 x 100	5.0	14.92	x		x	
100 x 100	6.0	17.71	x			
100 x 100	8.0	23.11	x			
100 x 100	10.0	28.26	x			
120 x 120	2.0	7.41	x			
120 x 120	3.0	11.02	x	x		
120 x 120	4.0	14.57	x			
120 x 120	5.0	18.06	x		x	
120 x 120	6.0	21.48	x			
120 x 120	8.0	28.13	x			
150 x 150	3.0	13.85	x			
150 x 150	4.0	18.34	x			
150 x 150	5.0	22.77	x			
150 x 150	6.0	27.13	x			
150 x 150	8.0	35.67	x			
150 x 150	10.0	43.96	x			
200 x 200	3.0	18.56	x			
200 x 200	5.0	30.62	x			
250 x 250	5.0	38.47	x			



WERNER FISCHER AG
STAHLROHRE

Rechteckrohre



diverse Legierungen

geschweisst, ungeglüht, metallblank, nach EN 10088, Stangenlänge ca. 6m

Abmessung	Wandstärke	Gewicht	1.4301	1.4301	1.4404
mm	mm	kg/m	blank	geschliffen	blank
20 x 10	1.0	0.44	x		
20 x 10	1.5	0.64	x	x	
20 x 15	1.5	0.75	x	x	
25 x 10	1.5	0.75	x	x	
25 x 15	1.5	0.87	x	x	
25 x 15	2.0	1.18		x	
30 x 10	1.5	0.87	x	x	
30 x 15	1.2	0.80		x	
30 x 15	1.5	0.99	x	x	x
30 x 15	2.0	1.29		x	
30 x 20	1.5	1.11	x	x	x
30 x 20	2.0	1.44	x	x	x
35 x 20	1.5	1.23	x	x	
35 x 20	2.0	1.60	x	x	
40 x 10	1.5	1.11	x	x	
40 x 10	2.0	1.44	x		
40 x 15	1.5	1.23	x	x	
40 x 15	2.0	1.65		x	
40 x 20	1.5	1.34	x	x	x
40 x 20	2.0	1.76	x	x	x
40 x 25	1.5	1.46	x		
40 x 30	1.5	1.58	x	x	
40 x 30	2.0	2.07	x	x	
40 x 30	3.0	3.01	x		
50 x 10	1.5	1.34	x		
50 x 15	1.5	1.46	x	x	
50 x 20	1.5	1.58	x		
50 x 20	2.0	2.07	x	x	x
50 x 25	1.5	1.70	x	x	x
50 x 25	2.0	2.23	x	x	x
50 x 30	1.5	1.81	x	x	
50 x 30	2.0	2.39	x	x	x
50 x 30	3.0	3.49	x	x	x
50 x 40	1.5	2.05	x	x	
50 x 40	2.0	2.70	x	x	
50 x 40	3.0	3.96	x		



WERNER FISCHER AG
STAHLROHRE

Rechteckrohre



diverse Legierungen

geschweisst, ungeglüht, metallblank, nach EN 10088, Stangenlänge ca. 6m

Abmessung	Wandstärke	Gewicht	1.4301	1.4301	1.4404
mm	mm	kg/m	blank	geschliffen	blank
60 x 10	1.5	1.58	x		
60 x 20	1.5	1.81	x		
60 x 20	2.0	2.39	x	x	
60 x 30	1.5	2.05	x	x	
60 x 30	2.0	2.70	x	x	x
60 x 30	3.0	3.96	x	x	x
60 x 40	1.5	2.28	x	x	
60 x 40	2.0	3.01	x	x	x
60 x 40	3.0	4.43	x	x	x
60 x 40	4.0	5.78	x		
70 x 40	2.0	3.33	x		
70 x 40	3.0	4.90	x		
80 x 10	1.5	2.05	x		
80 x 20	2.0	3.01	x	x	
80 x 30	3.0	4.90	x		
80 x 40	1.5	2.76	x	x	
80 x 40	2.0	3.64	x	x	x
80 x 40	3.0	5.37	x	x	x
80 x 40	4.0	7.03	x	x	
80 x 40	5.0	8.64	x		
80 x 50	2.0	3.96	x		
80 x 50	3.0	5.84	x	x	
80 x 50	4.0	7.74	x		
80 x 60	2.0	4.27	x	x	x
80 x 60	3.0	6.31	x	x	
80 x 60	4.0	8.29	x		
80 x 60	5.0	10.21	x		
100 x 40	2.0	4.27	x	x	x
100 x 40	2.5	5.30	x		
100 x 40	3.0	6.31	x	x	
100 x 40	4.0	8.26	x		
100 x 50	2.0	4.68	x	x	
100 x 50	3.0	6.95	x	x	x
100 x 50	4.0	9.09	x		
100 x 50	5.0	11.24	x		
100 x 60	2.0	4.99	x		
100 x 60	3.0	7.53	x	x	x



WERNER FISCHER AG
STAHLROHRE

Rechteckrohre



diverse Legierungen

geschweisst, ungeglüht, metallblank, nach EN 10088, Stangenlänge ca. 6m

Abmessung	Wandstärke	Gewicht	1.4301	1.4301	1.4404
mm	mm	kg/m	blank	geschliffen	blank
100 x 60	4.0	9.82	x		X
100 x 60	5.0	12.40	x		
100 x 80	2.0	5.60	x		
100 x 80	3.0	8.39	x		
100 x 80	4.0	11.05	x		
100 x 80	5.0	13.82	x		
120 x 40	2.0	4.99	x	X	
120 x 40	3.0	7.53	x	x	
120 x 40	4.0	9.82	x		
120 x 60	2.0	5.62	x	x	
120 x 60	3.0	8.39	x	x	x
120 x 60	4.0	11.06	x		
120 x 60	5.0	13.75	x		
120 x 80	2.0	6.28	x	x	
120 x 80	3.0	9.34	x	x	x
120 x 80	4.0	12.36	x		
120 x 80	5.0	15.38	x		
140 x 80	3.0	9.98	x		
140 x 80	4.0	13.50	x		
140 x 80	5.0	16.00	x		
150 x 50	2.0	6.40	x		
150 x 50	3.0	9.53	x	x	
150 x 50	4.0	12.40	x		
150 x 50	5.0	15.38	x		
150 x 80	3.0	10.70	x		
150 x 100	3.0	11.24	x		
150 x 100	5.0	18.40	x		
150 x 100	6.0	21.69	x		
160 x 80	3.0	10.94	x	x	
160 x 80	5.0	17.60	x		
200 x 100	3.0	13.82	x		
200 x 100	4.0	18.17	x		
200 x 100	5.0	22.40	x		
200 x 100	6.0	26.49	x		
250 x 150	5.0	30.04	x		



WERNER FISCHER AG
STAHLROHRE

Normenvergleich

Austenit – Cr-Ni / V2A

Werkstoff	Euronorm		USA	Frankreich
	EN 10088		ASTM	AFNOR
1.4301	1.4301	X5CrNi 18-10	304	Z 7 CN 18-09
1.4303	1.4303	X4CrNi 18-12	305L / 308	Z 5 CN 18-11 FF
1.4305	1.4305	X8rBi 18-9	303S	Z 8 CNF 18-09
1.4306	1.4306	X2CrNi 19-11	304L	Z 3 CN 18-10
1.4307	1.4307	X2CrNi 18-9		Z 2 CN 18-10
1.4311	1.4311	X2CrNi 18-10	304LN	Z 3 CN 18-10 Az
1.4541	1.4541	X6CrNiTi 18-10	321	Z 6 CNT 18-10
1.4550	1.4550	X6CrNiNb 18-10	347	Z 6 CN Nb 18-10

Austenit – Cr-Ni-Mo / V4A

Werkstoff	Euronorm		USA	Frankreich
	EN 10088		ASTM	AFNOR
1.4401	1.4401	X5CrNiMo 17-12-2	316	Z 7 CND 17-12-02
1.4404	1.4404	X2CrNi Mo 17-12-2	316L	Z 3 CND 18-12-02
1.4406	1.4406	X2CrNiMo 17-11-2	316LN	Z 3 CND 17-11 Az
1.4408	1)	GX5CrNiMo 19-11-2	CF-8M	---
1.4427	1)	X12CrNiMo 18-11	316F	---
1.4429	1.4429	X2CrNiMo 17-13-3	S 31'653	Z 3 CND 17-12 Az
1.4432	1.4432	X2CrNiMo 17-12-3	---	Z 3 CND 17-13-03
1.4435	1.4435	X2CrNiMo 18-14-3	316L	Z 3 CND 18-14-03
1.4435 BN2	1.4435 BN2	X2CrNiMo 18-14-3	316L	Z 3 CND 18-14-03
1.4436	1.4436	X3CrNiMo 17-13-03	316	Z 6 CND 18-12-03
1.4438	1.4438	X2CrNiMo 18-15-4	317L	Z 3 CND 19-15-04
1.4439	1.4439	X2CrNiMo 17-13-5	317LMN	Z 3 CND 18-14-05 Az
1.4466	1.4466	X1CrNiMo 25-22-2	S 31'050	Z 2 CND 25-22 Az
1.4571	1.4571	X6CrNiMoTi 17-12-2	316Ti	Z 6 CNDT 17-12

Hitze – und kriechbeständig

Werkstoff	Euronorm		USA	Frankreich
	EN 10088		ASTM	AFNOR
1.4828	1)	X15CrNiSi 20-12	309	Z 17 CNS 20-12
1.4841	1)	X15CrNiSi 25-21	S 31'500	Z 15 CNS 25-20

1) in EN 10088 nicht enthalten